MAGNETIC GRIPPER INSTALLATION SIZE HM1030

PRODUCT SPECIFICATIONS



► INCLUDED IN DELIVERY



Locking nut

C043910002


► RECOMMENDED ACCESSORIES




Straight Fittings - Quick Connect Style


GVM5

	► Technical Data
Order no.	HM1030NC
Adhesive force max. [N]	27
Operating pressure min. [bar]	3
Operating pressure max. [bar]	8
Operating temperature min. [°C]	5
Operating temperature max. [°C]	+80
Air volume per cycle [cm³]	3.5
Weight [kg]	0.06









MAGNETIC GRIPPER SERIES HM1000

PRODUCT ADVANTAGES



Secure hold during EMERGENCY STOP

Magnets attached to springs ensure your workpiece remains secure, even during a drop in pressure

Contact plate that increases friction value

The replaceable O-ring ensures the high dynamics in your application and protection of your workpiece

Residual holding force < 1N</p>

The demagnetised contact surface safeguards the process reliability of dropping off your workpiece

► THE BEST PRODUCT FOR YOUR APPLICATION



Our products welcome the challenge!

Extreme conditions, all over the world—our tried and tested components and systems give you endless possibilities. Find the best product for your specific use: www.zimmer-group.de



BENEFITS IN DETAIL



1 Mounting and positioning

- via centering sleeve and thread

2 Spring

- for piston return
- secured holding even in drop pressure

3 Permanent magnet

- requires no power supply
- high holding forces

(4) Transport safeguarding

(5) Robust, lightweight housing

- Hard-coated aluminum alloy

6 single-acting pneumatic cylinders

- only one pneumatic line required
- Spring return

7 Contact plate

- easy replaceable
- embedded O-ring to increase the friction coefficient

► FURTHER INFORMATION IS AVAILABLE ONLINE



► Technical Information

All information just a click away at: www.zimmer-group.com Find data, illustrations, 3D models and operating instructions for your installation size using the order number for your desired product. Quick, clear and always up-to-date.

